

◆ **Model No:** FSBB10050-0B07

- 50mm Transducer .
- 16.28mm Voice Coil SDHT.
- 25 μ PET Diaphragm.

◆ **Transducer front and side images:**



◆ **Specifications:**


Features:

Transducer	50CY-30 Ω +25C
Insert Molding	Molding ABS757
Injection Basket/Yoke	\varnothing 50mm ABS757
YOKE	\varnothing 20.2mm SPCC/CR3
Magnet	\varnothing 15.4mm NdFeB-N42
Washer (T-Plater)	\varnothing 15.6mm SPCC/CR3
PCB	\varnothing 16.72*5.3mm FR4
Diaphragm	\varnothing 48.6mmPET
Voice Coil	\varnothing 16.28mm SDHT
Grill Cover	NON
Mesh	Non-WovenY2 White

Transducers Properties:

Transducer	\varnothing 50mm
D.C.R.	30 \pm 15% Ω
Sensitivity	118 \pm 3dB (at 1KHz 1mW)
Frequency Response	20~20KHZ
Distortion	THD (50~6KHz) \leq 3%
Rated Input Power	20mW
Max Input Power	30mW
Buzz and Rattles	Shall Be Rated Input Power 20mW Program Source Or Sine Wave

◆ S. P. L Curve:



◆ Transducer front and side images:

